

PE1100N

Arm System, NVIDIA Jetson, LPDDR4, eMMC, USB3, Dual LAN, HDMI, M.2 E, M.2 M, M.2 B, AEM, Dual SIM, 12-24V

Features

- Intelligent Edge AI System with NVIDIA Jetson™ Orin™ NX, Orin™ Nano
- Fanless design and diverse I/O in a compact size
- Ready to connect Wi-Fi, BT & LTE by optional modules
- Wide range of power input and operating temperature
- Support ASUS Expansion Module (AEM)




Specifications

Processor System	SOM	Jetson Orin Nano 4G	Jetson Orin Nano 8G	Jetson Orin NX 8G	Jetson Orin NX 16G	
	CPU	6 x Arm® Cortex®-A78AE v8.2				8 x Arm® Cortex®-A78AE v8.2
	GPU	512-core NVIDIA Ampere GPU with 16 Tensor Cores	1024-core NVIDIA Ampere GPU with 32 Tensor Cores			
	Memory	4 GB 64-bit LPDDR5	8 GB 128-bit LPDDR5	8 GB 128-bit LPDDR5	16 GB 128-bit LPDDR5	
Wired Interface	Ethernet	2 x 10/100/1000 Mbps, RJ45				
	USB (or Header)	3 x USB 3.2 Gen1, Type-A 1 x USB 2.0, Micro-USB for OS Flash 2 x USB 2.0, Pin Header (Internal)				
	COM	2 x RS-232/422/485, DB9 1 x CAN bus, DB9				
	DIO	4 x DI, 4 x DO (2x5 Terminal Block, w/ isolation)				
	Display	1 x HDMI 1.4a, 3840 x 2160 @30Hz		1 x HDMI 2.0b, 3840 x 2160 @60Hz		
	Debug Port	1 x Debug console via Micro-USB				
Wireless Interface	Wi-Fi	Optional				
	Bluetooth	Optional				
	Cellular	Optional				
	GPS	Optional				
Expansion	M.2 M key	1 x 2242/2260/2280, for M.2 SSD (PCIe, OS disk, size option)				
	M.2 E key	1 x 2230, for Wi-Fi/BT (PCIe, USB 2.0, I2C and PCM)				
	M.2 B key	1 x 3042/3052, for 4G/5G (PCIe, USB 2.0/3.0)				
Slot	SIM	2 x nano-SIM slots				
Power	Power Input	12 to 24 VDC, 3-pin terminal block (1-pin for remote power button)				
Mechanical	Mounting	Wall-mount (support assembly with DIN rail clips)				
	Dimensions	Board: 3.5", 146 x 105 mm System: 152 x 114 x 72 mm				
	Weight	1.4 KG				
Environment	Operating Temp.	-20 ~ up to 60°C				
	Storage Temp.	-40 ~ 85°C				
	Relative Humidity	10 ~ 95% (non-condensing)				
Security	TPM	on-board TPM v2.0				
Others	Watch Dog Timer	Yes. HW WDT				
	Operating System ¹	Ubuntu Desktop				

Preliminary

Block Diagram



Ordering Information

PN	SoM	DRAM	Wi-Fi/BT* (M.2 E-Key)	SSD* (M.2 M-Key)	4G/5G* (M.2 B-Key)	O.P. Temperature	PSU*	OS*
PE1100N-SS100	Jetson Orin NX	16 GB	option	option	option	-20~60	option	option
PE1100N-SS70	Jetson Orin NX	8 GB	option	option	option	-20~60	option	option
PE1100N-SS40	Jetson Orin Nano	8 GB	option	option	option	-20~60	option	option
PE1100N-SS20	Jetson Orin Nano	4 GB	option	option	option	-20~60	option	option

Packing List

Description	Qty
Adapter cable DC to terminal block 3 pin	1
Wall mount bracket set	1
DIO terminal block	1
Dust cover set	1

Optional Accessories: (purchased separately)

Item#	Description
Wi-Fi/BT Module	
0C011-00214100	EMWICON WMX6219, RTL8822CE, Wi-Fi 5 802.11ac + BT 5.0 (2*2), M.2 2230
4G Module	
TBD	
5G Module	
TBD	
Wi-Fi/BT ANTENNA	
14008-04490000	
4G ANTENNA	
TBD	
5G ANTENNA	
TBD	
SSD	
03B03-00236400	SSD P3X4 128GB M2 2280 NVME
03B03-00422100	SSD P3X4 256GB M2 2280 NVME
03B03-00378200	SSD P3X4 512GB M2 2280 NVME

* The part number might vary due to part number revision.

Optional Accessories: (purchased separately)

Item#	Description
ADAPTER	
0A001-01050900	65W Power adapter, input 100 - 240Vac, output 12Vdc / 5.41A, C14, 0 to 40°C O.P. temperature
0A001-00891600	65W Power adapter, input 100 - 240Vac, output 19Vdc / 3.42A, C6, 0 to 35°C O.P. temperature
POWER CORD	
14009-00021400	C14 Power cord with United States (US) plug, 180cm
14009-00021000	C14 Power cord with Europe (EU) plug, 180cm
14009-00021100	C14 Power cord with China (CN) plug, 180cm
14009-00020600	C14 Power cord with Japan (JP) plug, 180cm
14009-00020800	C14 Power cord with Australia (AU) plug, 180cm
14009-00020900	C14 Power cord with United Kingdom (UK) plug, 180cm
14009-00021000	C14 Power cord with Korea (KR) plug, 180cm
14009-00020700	C14 Power cord with Swiss (CH) plug, 180cm
14009-00021200	C14 Power cord with Taiwan (TW) plug, 180cm
14G1100083A0	C6 Power cord with United States (US) plug, 150cm
14G110060341	C6 Power cord with Europe (EU) plug, 80cm
14G110008300	C6 Power cord with China (CN) plug, 80cm
14G110008330	C6 Power cord with Japan (JP) plug, 80cm
14G110060365	C6 Power cord with Australia (AU) plug, 80cm
14G110008350	C6 Power cord with United Kingdom (UK) plug, 80cm
14G110008310	C6 Power cord with Korea (KR) plug, 80cm
14G1100083E0	C6 Power cord with Swiss (CH) plug, 80cm
14G11006032B	C6 Power cord with Taiwan (TW) plug, 80cm

* The part number might vary due to part number revision.